

1. SIGN BLADES SHALL BE 0.080 INCH THICK SHEET METAL ALUMINUM WITH HIGH INTENSITY PRISMATIC SHEETING.
2. SIGN FACE SHALL BE GREEN WITH A 1/2-INCH THICK WHITE BORDER.
3. ALL LETTERING SHALL BE WHITE CAPITAL LETTERS.
4. TWO (2) IDENTICAL SIGN BLADES SHALL BE PROVIDED FOR EACH SIGN, AND SHALL BE MOUNTED BACK TO BACK ON THE POST USING RIVETS AND PVC SPACERS AS SHOWN.
5. SIGN POST SHALL BE 10-FOOT TALL, 1.75-INCH SQUARE GALVANIZED STEEL POST (14 GAUGE).
6. BREAKAWAY BASE SHALL CONSIST OF A 3-FOOT TALL, 2-INCH SQUARE GALVANIZED STEEL POST (12 GAUGE).

NOTES:


R=3/4"

1/2" THICK WHITE BORDER


5/16" DRIVE RIVETS FOR POST MOUNTING (TYP.)

1 7/8" - 2 1/4" RIVETS WITH PVC SPACER FOR BACK TO BACK SIGN MOUNTING (TYP.)

VARIES



SCALE : NONE
DRAWN BY: SR
CHECKED BY: SMB
APPROVED BY: DAP
LAST REVISED: 4/29/2008



TOWN OF GLASTONBURY
DEPARTMENT OF PHYSICAL SERVICES
ENGINEERING DIVISION

STREET NAME SIGN
AND POST DETAILS